

PowerMount Aggressor - Product Specification

1. WALL STRUCTURE - Entire wall mount structure shall be constructed of 2" square tubing. Structure shall be designed to allow for a wall-to-backboard offset of 12". Wall structure shall be designed to accommodate any backboard with an industry standard 20"x 35" backboard mounting pattern. All mounting brackets shall be no less than 1/4" thick and all hardware shall be grade 5 zinc plated. Structure shall be finished with black powder coat paint. Steel structure shall be attached to support wall with fasteners provided by installer.

2. BACKBOARD - Backboard shall be approximately 42"x 60" rectangular steel. Skin shall be 10 gauge steel with 1/4" thick vertical struts and 3/16" thick center rim support channel. Slotted attachment brackets shall be fully welded on the backside providing an industry standard 20"x 35" mounting. Rim mounting shall be 5"x5". Backboard shall have a white powder coat finish, and have an official orange shooters square.

3. GOAL DESIGN - Flexible type so as to absorb the stress of player contact. The rim shall be of institutional quality with an official 5/8" diameter ring. Ring opening diameter shall be the standard 18" I.D. Rim shall have an orange powder coated finish. Heavy-duty nylon net shall be provided.

4. WARRANTY - Entire system shall carry a Lifetime Limited Warranty. Shipping weight shall be approximately 200#.