



**Basketball-Goals.com**

67 CANTERBURY LANE - SOUTHTON, CT 06489  
TOLL FREE - 866-892-7277 - FAX 775-822-1858  
INTERNATIONAL CALLS 860-621-7321  
EMAIL: BASKETBALLGOALS@AOL.COM  
WEB SITE: WWW.BASKETBALL-GOALS.COM

## CARPETDECK

### PRODUCT SPECIFICATIONS

PRODUCT COMPOSITION	STANDARD / NORMS	DATA
Manufacturing Process	ISO 2424	Needle Felt
Surface Aspect	ISO 2424	Patterned
Pile yarn composition	CEE 83/623	100% polypropylene
Primary Backing	ISO 2424	Bitumen

### PRODUCT DIMENSIONS

Pile Height (+ or -0.5mm)	ISO 1766	.25 in.
Total Height (+ or -7.5%)	ISO 1766	.38 in.
Pile Weight (+ or -7.5mm)	ISO 8543	33.9 oz/sy
Total Weight (+ or -7.5%)	ISO 8543	131 oz/sy
Total Size (+ or -0.2%)	ISO 3018	19 11/16" x 19 11/16"

### ELECTROSTATIC PROPERTIES

Dimensional Stability	EN 986	Pass
Walk on test	ISO TR 6356	<2 KV (IBM/ICL)
Electrical Resistivity Vertical & Horizontal	DIN 54345	
Sound Insulation:	ISO 140-8	> or = 24 db
Thermal Retention:	ISO 8302	0.12m2KW

### COLOR FASTNESS

To Light:	ISO 105 B02	> or = 6
To Water:	ISO 105 E01	5
To Shampoo:	BS 1006	4-5
To Rubbing dry & wet	ISO 105 x 12	4-5 dry/wet

### FLAMMABILITY RATING

Flooring Radiant Panel Test	ASTM E648/DIN 4102/CPSC FF 1-70	Passes Federal Flammability Standard
Pill Test	ISO 6925 / ASTM D 2829	Pass
Hot Metal Nut Test	BS 4790 / BS 5287	Low Radius
Coefficient of Friction wet & dry	ASTM - C 1028-89	Wet .63; Dry .65

### CLEANING AND MAINTENANCE

**Daily:** Vacuum daily with a commercial grade vacuum cleaner that features a rotary power brush or beater bar. Mats release more soil when completely dry.

#### Periodic Maintenance:

Out matting products clean beautifully with the use of a Hot Water Extraction machine. Minimum quarterly intervals recommended for high traffic applications. For optimum performance during winter months, traffic lanes may require more frequent extraction cleaning depending on weather conditions and climate.

### WARRANTY

#### Limited 3-Year Abrasive Warranty

Offers a limited warranty for abrasive wear on indoor installations. Warranty requires product installation over a dry,