

Jam Turbo Basketball System

1. **VERTICAL POLE** - Vertical pole shall be one-piece 4" square (sectional posts not considered equal) with a minimum 11 gauge wall thickness and allow for burying 36" in concrete. Posts with thinner wall thickness are not considered equal. Posts intended to be buried less than 36" are not considered equal. Pole shall have a watertight vinyl cap to seal out moisture.
2. **EXTENSION ARMS** - Adjustable extension arms shall be constructed of dual 2" x 2" tubing. Extension shall allow for a minimum 24" from front of post to face of backboard with rim at 10' playing height. The height adjustment crank cylinder shall have a minimum 2000# capacity rating. Pole structure design shall allow for rim height to be adjusted infinitely from 10' down to 7'. Two springs mounted in the extension assembly shall be included to minimize the amount of effort required to adjust the goal height when raising or lowering the unit. Pole design shall permit the rim to be mounted directly to the extension arm through the backboard so as to reduce stress on the backboard. An easy-to-read height adjustment label shall register rim height.
3. **BACKBOARD** – Constructed of 1/4" thick clear tempered glass with bright white ceramic markings fired into the glass. The framework shall be constructed from clear anodized aluminum "L" type extrusions. Overall backboard size shall be approximately 54" wide and 36" high.
4. **RIM** - Standard rim shall be of a flexible type so as to absorb the stress of player contact. Spring action shall be provided by a heavy duty compression wire spring. A steel coverplate must enclose entire internal mechanism. All structural components shall be built of no less than 3/16" steel. Rim shall be of institutional quality with an official 5/8" diameter high strength steel ring supported by a 3/16" brace supporting 60% of the ring. Rim shall be punched to mount either a 3"x 4" or 5"x 5" hole pattern. Orange powdercoated finish.
5. **WARRANTY** - Pole, backboard, and standard rim shall carry Lifetime Superior Warranty. Entire system weight shall be approximately 205#.