TECHNICAL SPECIFICATIONS

Max. Weight of Suspended Load	1000 lbs / 450 kg.*
Load Type	Vertical suspended or pivoted load.
Strap Breaking Strength	7300 lbs / 3318 kg (the rest of the unit has a higher ultimate strength).
Strap Length	40 ft / 11.7 m.
Operating Principle	Fail safe, self-checking mechanical mechanism.
Tripping Speed-Sudden Free-Fall	1.5 ft per second / 0.46 meters per second.
Tripping Speed, Slopping or Back Drive Condition	1.5 ft per second / 0.46 meters per second.
Re-Set Action	Automatic on lifting the load approximately one inch.
Weight (As Shipped)	17 lbs / 8 kg.

PL 1000 SAFETY STRAP

- The Posilok Safety Strap has been cycled tested to 30 years of typical gymnasium usage with no significant wear or deterioration of the unit.
- The Posilok Saftey Strap has a modern attractive appearance and is finished with durable e-coat paint.
- The strap has a visible “maximum extension” indicator.

WARNING

***This is the maximum weight allowable for the suspended object that the Posilok strap is protecting.**

The Posilok Safety Strap is designed to safely arrest a falling object of this weight.

The actual forces on the strap and Posilok device will be much higher than this when it is stopping the falling object. It is designed to absorb these forces.



Call to speak with an expert:

1-866-829-4411

or visit us online:

TORKWINCH.COM

USA: Tork Winch USA LLC
5020 Hazel Jones Road
Bossier City, LA | 71111

CANADA: Torkwinch
125 Bysham Park Drive
Woodstock, ON | N4T 1P1

P: 1-866-829-4411
E: sales@torkwinch.com
F: 1-519-539-9191